



YETDA INDUSTRY LTD.

3" 7.62mm 5*8 GREEN DOT MATRIX DISPLAY

M-30581AGU11

DESCRIPTION

- * 3" (80.01mm) Inch Matrix Height.
- * High Bright Green Dot Matrix.
- * Black Face and White Dot Color.
- * Row Common Cathode.

ABSOLUT MAXIMUM RATINGS AT Ta=25°C

Parameter		UNIT
Power Dissipation Per Dot	80	mW
Peak Forward Current Per Dot	120	mA
Forward current Per Dot (Static)	30	mA
Reverse Voltage Per Dot	10	V
Operation Temperature Range	-25°C TO +80°C	°C
Storage Temperature Range	-25°C TO +100°C	°C
Lead Soldering Temperature	260°C for 3 seconds 1.6mm(1/16 inch) from body	


ELECTRICAL/OPTOTICAL CHARACTERISTIC AT Ta=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITION
Average Luminous Intensity	Iv	6	9		mcd	If=20mA
Peak Emission Wavelength	λd		573		nm	If=20mA
Forward Voltage Per Dot	Vf		2.2	2.6	V	If=20mA
Reverse Current Per Dot	Ir			10	uA	Vr=10V
Luminous Intensity Matching Ratio	Iv-m	2 : 1				If=20mA




YETDA INDUSTRY LTD.

P.C.B. Pin Connection



Reflector Dimensions

Item#-3058X
Unit:mm



Unit:mm