



# YETDA INDUSTRY LTD.

## 4.6" 10mm 5\*8 RED & GREEN DOT MATRIX DISPLAY

### M-46581ASKGU11

#### DESCRIPTION

- \* 4.6" (106.68mm) Inch Matrix Height.
- \* High Bright Red & Green Dot Matrix.
- \* Black Face and White Dot Color.
- \* Row Common Cathode.

#### ABSOLUT MAXIMUM RATINGS AT Ta=25°C

Parameter		UNIT
Power Dissipation Per Dot	80	mW
Peak Forward Current Per Dot	120	mA
Forward current Per Dot (Static)	30	mA
Reverse Voltage Per Dot	10	V
Operation Temperature Range	-25°C TO +80°C	°C
Storage Temperature Range	-25°C TO +100°C	°C
Lead Soldering Temperature	260°C for 3 seconds 1.6mm(1/16 inch) from body	

#### ELECTRICAL/OPTICAL CHARACTERISTIC AT Ta=25°C

##### RED

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITION
Average Luminous Intensity	Iv	4	12		mcd	If=20mA
Peak Emission Wavelength	λ d		660		nm	If=20mA
Forward Voltage Per Dot	Vf		3.6	4.4	V	If=20mA
Reverse Current Per Dot	Ir			10	uA	Vr=10V
Luminous Intensity Matching Ratio	Iv-m	2 : 1				If=20mA

#### ELECTRICAL/OPTICAL CHARACTERISTIC AT Ta=25°C


##### YELLOW GREEN

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITION
Average Luminous Intensity	Iv	6	9		mcd	If=20mA
Peak Emission Wavelength	λ d		573		nm	If=20mA
Forward Voltage Per Dot	Vf		4.4	5.2	V	If=20mA
Reverse Current Per Dot	Ir			10	uA	Vr=10V
Luminous Intensity Matching Ratio	Iv-m	2 : 1				If=20mA




# YETDA INDUSTRY LTD.

## P.C.B. Pin Connection



## Reflector Dimensions



Unit:mm