

YETDA INDUSTRY LTD.

Technical Data Sheet

MODEL NO : Q115ANR/ANY4

Features :

- Package in 8mm tape on 7" diameter reel
- Compatible with automatic placement equipment
- Compatible with reflow solder process


Applications :

- Indicators
- Automotive : backlighting in dashboard and switch
- Backlight for LCD

Dice material	Emitted color	Lens Color
AlGaInP/GaAs	Red	Water transparent
AlGaInP/GaAs	Yellow	

Electrical/Optical Characteristics(Ta=25°C)

Parameter	Test Condition	Symbol	Value			Unit	
			Min	Typ	Max		
Spectral half bandwidth	I _F =20mA	$\Delta \lambda$	R		19	nm	
			Y		17		
Dominant wavelength	I _F =20mA	λ_D	R	630	640	650	nm
			Y	585	590	595	
Forward voltage	I _F =20mA	V _F	R	1.7	2.0	2.5	V
			Y	1.7	2.0	2.5	
Luminous intensity	I _F =20mA	I _v	R	50	85	160	mcd
			Y	100	170	320	
Viewing angle at 50% I _v	I _F =10mA	2 θ 1/2		150		Deg	
Reverse current	V _R =5V	I _R			10	μ A	








YETDA INDUSTRY LTD.


Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Value			Unit
		R	Y		
Power dissipation	Pd	75	75		mW
Forward current	I _F	30			mA
Reverse voltage	V _R	5			V
Operating temperature range	T _{op}	-40 ~+80			°C
Storage temperature range	T _{stg}	-40 ~+85			°C
Peak pulsing current (1/8 duty f=1kHz)	I _{FP}	125			mA

PACKAGING DIMENSIONS (mm):

RECOMMEND PAD LAYOUT






YETDA INDUSTRY LTD.

Feeding Direction	Dimensions of Reel (Unit: mm)

Dimensions of Tape (Unit: mm)	

Arrangement of Tape	


NOTES
<ol style="list-style-type: none"> 1. Empty component pockets are sealed with top cover tape; 2. The maximum number of missing lamps is two; 3. The polarity mark is oriented towards the tape sprocket hole ; 4. 3,000(Max)pcs/Reel 5. .Packing will be multiple of 500, e.g 500pcs/R, 1000pcs/R, 1500pcs/R..etc , MAX 3000pcs/R



YETDA INDUSTRY LTD.


Precautions For Use :
Over - current - proof
Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen)
Storage
1. The operation of temperature and R.H. are : $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, 60%R.H. Max.
2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a dampproof box with desiccating reagent. Considering the tape life, we suggest our customers to use our products within 1.5 year (from production date) .
3. It's recommended to bake before soldering when the package is unsealed after 72 hrs. The condition is : $60^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 15hrs.

■ Reflow Temp/Time



NOTES:

1. We recommend the reflow temperature $245^{\circ}\text{C} (\pm 5^{\circ}\text{C})$. the maximum soldering temperature should be limited to 260°C .
2. dont cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.




YETDA INDUSTRY LTD.

■Soldering iron

Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1\text{sec}$). Power dissipation of iron should be smaller than 20W, and temperatures should be controllable. Surface temperature of the device should be under 230°C .

■Rework

1. Customer must finish rework within 5 sec under 260°C .
2. The head of iron can not touch copper foil
3. Twin-head type is preferred.



- Avoid rubbing or scraping the resin by any object, during high temperature, for example reflow 、 solder etc.