



YETDA INDUSTRY LTD.

Technical Data Sheet

MODEL NO : S5050ANW4P-CF

5050 Package 5.0*5.0mm TOP SMD

Features :

- Package in 8mm tape on 7" diameter reel
- Compatible with automatic placement equipment
- Compatible with reflow solder process

Applications :

- Lighting
- Automotive : backlighting in dashboard and switch
- Backlight for LCD

Dice material	Emitted color	Lens Color
InGaN	White	Yellow Diffused

Electrical/Optical Characteristics(Ta=25°C)

Parameter	Test Condition	Symbol	Value			Unit
			Min	Typ	Max	
Color Temperature	I _F =350mA	CCT	6000		6500	K
Forward voltage	I _F =350mA	V _F	3.0	.	3.4	V
Chromaticity Coordinates		X		0.290		
		Y		0.300		
Luminous Flux	I _F =350mA	Lm	120		135	Lm
Viewing angle at 50% Iv	I _F =350mA	2θ 1/2	--	120	--	Deg
Color Index	I _F =350mA	Ra	70			
Reverse current	V _r =5V	I _R	--	∅ -	10	μA


Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Value	Unit
		White	
Power dissipation	Pd	1.5	W
Forward current	I _F	350	mA
Reverse voltage	V _R	5	V
Operating temperature range	Top	-35 ~+85	°C
Storage temperature range	Tstg	-40 ~+100	°C
Peak pulsing current (1/8 duty f=1kHz)	I _{FP}	400	mA

2018AUG28Y



PACKAGING DIMENSIONS





YETDA INDUSTRY LTD.

Precautions For Use :

Over - current - proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen)


Storage

1. The operation of temperature and R.H. are : $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, 60%R.H. Max.
2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a dampproof box with desiccating reagent. Considering the tape life, we suggest our customers to use our products within 1.5 year (from production date) .
3. It's recommended to bake before soldering when the package is unsealed after 72 hrs. The condition is : $60^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 15hrs.

■ Reflow Temp/Time

■ Temperature-profile (Surface of circuit board)

Use the following conditions shown in the figure.



NOTES:


1. We recommend the reflow temperature $245^{\circ}\text{C} (\pm 5^{\circ}\text{C})$. the maximum soldering temperature should be limited to 260°C .
2. dont cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

■ Soldering iron

Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1\text{sec}$). Power dissipation of iron should be smaller than 20W, and temperatures should be controllable . Surface temperature of the device should be under 230°C .



YETDA INDUSTRY LTD.



- Avoid rubbing or scraping the resin by any object, during high temperature, for example reflow 、 solder etc.