



YETDA INDUSTRY LTD.

Technical Data Sheet

MODEL NO : S5630ANWW4P-PLK

(0.5W) 05630 5.6 x 3.0mm Warm White SMD

Features :

- Package in 8mm tape on 7" diameter reel
- Compatible with automatic placement equipment
- Compatible with reflow solder process

Applications :

- Indicators
- Automotive : backlighting in dashboard and switch
- Backlight for LCD

Dice material	Emitted color	Lens Color
InGaN	Warm White	Yellow Diffused

Electrical/Optical Characteristics(Ta=25°C)

Parameter	Test Condition	Symbol	Value			Unit
			Min	Typ	Max	
Forward voltage	If=150mA	Vf	3.0	.	3.4	V
Luminous intensity	If=150mA	Iv	24000		25500	mcd
Luminous Flux	If=150mA	φ	80		85	
Color Temperature	If=150mA	TC	2900	3000	3200	K
Viewing angle	If=150mA	2θ 1/2	--	120	--	Deg
Reverse current	Vr=5V	Ir	--	--	10	μA

Absolute Maximum Ratings(Ta=25°C)


Parameter	Symbol	Value	Unit
		White	
Power dissipation	Pd	500	mW
Forward current	If	150	mA
Reverse voltage	Vr	5	V
Operating temperature range	Top	-20 ~+80	°C
Storage temperature range	Tstg	-40 ~+80	°C
Peak pulsing current (1/8 duty f=1kHz)	Ifp	300	mA

2018SEP8Y




YETDA INDUSTRY LTD.

PACKAGING DIMENSIONS






YETDA INDUSTRY LTD.




All dimensions in mm, tolerances unless mentioned is ± 0.1 mm.

Details Of Carrier Tape



A: Top Cover Tape, 300mm; B: Leader, Empty, 200mm; C: 4000 Lamps Loaded; D: Trailer, Empty, 200mm.

Reel Dimension







YETDA INDUSTRY LTD.

Typical Electro-Optical Characteristics Curve:


Volt-Ampere Characteristics




Relative Luminous Intensity VS Forward Current




Forward Current Derating Curve




Luminous Intensity VS Ambient Temperature



Relative Spectral Distribution



Typical Spectral Distribution





YETDA INDUSTRY LTD.

Precautions For Use :


Over - current - proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen)

Storage

1. The operation of temperature and R.H. are : $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, 60%R.H. Max.
2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a dampproof box with desiccating reagent. Considering the tape life, we suggest our customers to use our products within 1.5 year (from production date) .
3. It's recommended to bake before soldering when the package is unsealed after 72 hrs. The condition is : $60^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 15hrs.

■ Reflow Temp/Time



NOTES:

1. We recommend the reflow temperature $245^{\circ}\text{C} (\pm 5^{\circ}\text{C})$. the maximum soldering temperature should be limited to 260°C .
2. dont cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.




YETDA INDUSTRY LTD.

■Soldering iron

Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1\text{sec}$). Power dissipation of iron should be smaller than 20W, and temperatures should be controllable. Surface temperature of the device should be under 230°C .

■Rework

1. Customer must finish rework within 5 sec under 260°C .
2. The head of iron can not touch copper foil
3. Twin-head type is preferred.



- Avoid rubbing or scraping the resin by any object, during high temperature, for example reflow, solder etc.