







# YETDA INDUSTRY LTD.

## 10W HIGH POWER RGB LED (EMITTER) RGB111E-9V

Features	Applications
* Long operating life	* Reading lights (car, bus, aircraft)
* Highest flux	* LCD Backlights/light Guides
* Available in RGB	* Fiber optic alternative/ Decorative Entertainment
* Lambertian radiation pattern	* Mini-accent/Up lighters/Down lighters/ Orientation
* More energy efficient than incandescent and most halogen lamps	* Indoor/Outdoor commercial and Residential Architectural
* Low voltage DC operated	* Cove/Under shelf/Task
* Cool beam, safe to the touch	* Bollards/Security/Garden
* Instant light (less than 100ns )	* Portable (flashlight, bicycle)
* Fully dimmable	* Edge-lit signs (Exit, point of sale)
* No UV	* Automotive Exit (Stop-Tail-Turn,CHMSL, Mirror Side Repeat)
* Superior ESD protection	* Traffic signaling / Beacons / Rail Crossing and Wayside
* Eutectic die bonding	
* RoHS compliant	

### PACKAGE





# YETDA INDUSTRY LTD.

## Typical Optical/ Electrical Characteristics @T<sub>J</sub>=25°C

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V <sub>FR</sub>	I <sub>F</sub> =350mA	6.0		7.2	V
	V <sub>FG</sub>		9		10.2	
	V <sub>FB</sub>		9		10.2	
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =5V	0		1	uA
Viewing Angle	2θ <sub>1/2</sub>	I <sub>F</sub> =350mA		140		deg
Luminous Intensity	φ <sub>VR</sub>	I <sub>F</sub> =350mA	90	-	120	lm
	φ <sub>VG</sub>		180		220	
	φ <sub>VB</sub>		30		50	
Wavelength	λ <sub>dR</sub>	I <sub>F</sub> =350mA	620		625	nm
	λ <sub>dG</sub>		520		525	
	λ <sub>dB</sub>		460		465	

### Notes:

1. Tolerance of measurement of forward voltage±0.1V.
2. Tolerance of measurement of peak Wavelength±2.0nm.
3. Tolerance of measurement of luminous intensity±15%.

### Absolute Maximum Rating

Item	Symbol	Absolute Maximum Rating	Unit
DC Forward Current	I <sub>F</sub>	1100	mA
Reverse Voltage	V <sub>R</sub>	5	V
Operation Temperature	T <sub>OPR</sub>	-30~+60	°C
Storage Temperature	T <sub>STG</sub>	-40~+90	°C
Lead Soldering Temperature*	T <sub>SOL</sub>	Max. 260°C for 3sec Max.	

\*IFP Conditions : Pulse Width≤10msec duty≤1/10

\* All high power emitter LED products mounted on aluminum metal-core printed circuit board, can be lighted directly, but we do not recommend lighting the high power products for more than 5 seconds without a appropriate heat dissipation equipment.

\* Re-flow, wave peak and soak- stannum soldering etc.is not suitable for this products.

\* Suggest to solder it by professional high power LED soldering machine.

\* Can use invariable-temperature searing-iron with soldering condition≤260 degree less than 3 seconds.