

YETDA INDUSTRY LTD.

Technical Data Sheet

MODEL NO : Q3014Y4-PL

3014Package 3.0*1.4mm Chip LEDs

Features :

- Package in 8mm tape on 7" diameter reel
- Compatible with automatic placement equipment
- Compatible with reflow solder process


Applications :

- Indicators
- Automotive : backlighting in dashboard and switch
- Backlight for LCD

Dice material	Emitted color	Lens Color
AlGaInP/GaAs	YELLOW	Water Clear

Electrical/Optical Characteristics(Ta=25°C)

Parameter	Test Condition	Symbol	Value			Unit
			Min	Typ	Max	
Spectral half bandwidth	I _F =20mA	$\Delta \lambda$		22		nm
Dominant wavelength	I _F =20mA	λ_D	588		592	nm
Forward voltage	I _F =20mA	V _F	1.8		2.4	V
Luminous intensity	I _F =20mA	I _v	600		800	mcd
Viewing angle at 50% I _v	I _F =20mA	2 θ 1/2		120		Deg
Reverse current	V _R =5V	I _R			10	μA




YETDA INDUSTRY LTD.

Absolute Maximum Ratings($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Power dissipation	P_d	96	mW
Forward current	I_F	20	mA
Reverse voltage	V_R	5	V
Operating temperature range	T_{op}	$-20 \sim +80$	$^{\circ}\text{C}$
Storage temperature range	T_{stg}	$-40 \sim +80$	$^{\circ}\text{C}$
Peak pulsing current (1/8 duty $f=1\text{kHz}$)	I_{FP}	60	mA

PACKAGING DIMENSIONS (mm):




1. All dimension units are millimeters.

2. All dimension tolerance is $\pm 0.15\text{mm}$ unless otherwise noted.




注意：操作時應注意靜電




YETDA INDUSTRY LTD.


Typical optical characteristics curves




Relative Intensity vs. Wavelength




Forward current vs. Forward voltage




Forward current Derating Curve




Relative Luminous Intensity vs. Forward Current



Luminous Intensity vs. Ambient Temperature




Radiation Diagram



YETDA INDUSTRY LTD.


Precautions For Use :
Over - current - proof
Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen)
Storage
1. The operation of temperature and R.H. are : $5^{\circ}\text{C} \sim 30^{\circ}\text{C}$, 60%R.H. Max.
2. Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a dampproof box with desiccating regent. Considering the tape life, we suggest our customers to use our products within 1.5 year (from production date) .
3. It's recommended to bake before soldering when the package is unsealed after 72 hrs. The condition is : $60^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 15hrs.

■ Reflow Temp/Time



NOTES:

1. We recommend the reflow temperature $245^{\circ}\text{C} (\pm 5^{\circ}\text{C})$. the maximum soldering temperature should be limited to 260°C .
2. dont cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.




YETDA INDUSTRY LTD.

■Soldering iron


Basic spec is $\leq 5\text{sec}$ when 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1\text{sec}$). Power dissipation of iron should be smaller than 20W, and temperatures should be controllable. Surface temperature of the device should be under 230°C .

■Rework

1. Customer must finish rework within 5 sec under 260°C .
2. The head of iron can not touch copper foil
3. Twin-head type is preferred.






- Avoid rubbing or scraping the resin by any object, during high temperature, for example reflow 、solder etc.




YETDA INDUSTRY LTD.

■Feeding Direction


● Dimensions of Reel (Unit: mm)



Carrier Tape



■Dimensions of Tape (Unit: mm)



A : 蓋帶，300 mm；B : 引導，空帶，200mm；C : 編載產品 4000只；D : 尾部，空帶，200mm
A: Top Cover Tape, 300mm; B: Leader, Empty, 200mm; C: 4000 Lamps Loaded; D: Trailer, Empty, 200mm.

■Note

1. Empty component pockets are sealed with top cover tape;
2. The maximum number of missing lamps is two.
3. 4,000 pcs/Reel.